




Certified

Feature

- ❑ Fully Automatic Operation System
 - Sensing water level in boiling chamber to protect heater from over heating
 - Sensing water supply to control distillation process
 - Sensing water level in reservoir to start and stop distillation automatically
- ❑ Easy to use and maintenance free
- ❑ Built-in Large Storage Tank for Distilled Water, Ready for Use
- ❑ Safety devices with over current leakage breaker and water level switch



MODEL	LWD-3004	LWD-3008	LWD-3012
Dimensions (W x D x Hmm)	680 x 340 x 530	760 x 340 x 610	700 x 400 x 650
Capacity	4.0ℓ / hour	8.0ℓ / hour	12.0ℓ / hour
Heater	3kW	6kW	9kW
Cooling Water	Approx. 30 ~ 50ℓ	Approx. 60 ~ 80ℓ	Approx. 80 ~ 100ℓ
Material	Interior	Stainless Steel Boiler Stainless Steel Storage Tank	
	Exterior	Powder Coating Steel Case	
Reservoir	8ℓ SUS Storage Tank	14ℓ SUS Storage Tank	19ℓ SUS Storage Tank
Operation		Fully Automatic Operation	
Signal Lamp		Distill, Full, Water	
Safety		Over Temp Protector Water Float Level Sensor Water Supply Cut Off	
Electric supply		220V 50/60Hz	

 Custom made order is available
Specifications can be changed without prior notice for quality improvement.