

# Automatic Double Water Still



## Feature

- ❑ Fully Automatic Operation System
  - Sensing water level in boiling chamber to protect heater from over heating
  - Sensing water supply to control distillation process
  - Sensing water level in reservoir to start and stop distillation automatically
- ❑ Easy to use and maintenance free
- ❑ Built-in Large Storage Tank for Distilled Water, Ready for use
- ❑ Safety devices with over current leakage breaker and water level switch



MODEL		LWD-3005D	LWD-3010D
Dimensions	(W x D x Hmm)	570 x 600 x 600	680 x 720 x 650
Capacity		4.0ℓ / hour	8.0ℓ / hour
Heater		6kW	12kW
Cooling Water		Approx. 35 ~ 60ℓ	Approx. 60 ~ 90ℓ
Material	Interior	Stainless Steel Boiler Stainless Steel Storage Tank Powder Coating Steel Case	
	Exterior		
Reservoir		8ℓ SUS Storage Tank	14ℓ SUS Storage Tank
Operation		Fully Automatic Operation	
Signal Lamp		Distill, Full, Water	
Safety		Over Temp Protector Water Float Level Sensor Water Supply Cut Off	
Electric supply		220V 50/60 Hz	



Custom made order is available  
Specifications can be changed without prior notice for quality improvement.